



# pivot bed Tow DOLLY

Part #

2050-1



## Specifications

- Minimum tire width: 34" inside to inside
- Maximum tire width: 77" outside to outside\*
- Overall length: 121"
- Overall width: 102"
- Height at fenders: 29"
- Weight — empty: 545 pounds
- Adjustable TieDown straps: fit 12" - 16" tires
- Maximum weight of towed vehicle: 4,250 pounds
- Trailer ball size: 2"

*Roadmaster's value priced dolly with features usually only found on more expensive models*

### Adjustable Deck

Deck swivels 9° for easy cornering.

### Adjustable TieDowns

One size adjusts to fit tires from 12" to 16".

### Accu-Lube™ hubs


Easily repack the bearings through the grease fitting.

### Heavy-duty trailer tires

...Increase safety when towing heavier vehicles.

### Electric brakes

Built in electric brakes for safer stops.



## Economical but feature packed —

- Slideable 'Easy-load' ramps quickly adjust your dolly to tow almost any car, large or small, weighing up to 4,250 pounds.
- Unique TrueGrip laser-cut pattern on ramps provides positive traction in both directions for safe loading and unloading
- Deck swivels 9° for easy cornering and maneuvering
- Ramps, axle and deck are powder coated for maximum durability
- Easy assembly (average assembly time: one to two hours)
- Complete with adjustable TieDown™ straps (fit most tires from 12 to 16 inches) and ratchets

\*Regardless of the tire width, test to ensure that the towed vehicle will not come into contact with the dolly's fenders before towing. Vehicles with fender flares, or with fenders that overhang the wheels, may be susceptible to damage of this kind.

800-669-9690 • [www.roadmasterinc.com](http://www.roadmasterinc.com)